

FM-200®

Gaseous Fire Suppression Systems

Fast, clean & safe fire protection

FM-200[®] systems are internationally accepted as providing reliable and effective fire protection solutions for high value assets, processes and locations, as well as the people who work in these protected areas.







Electrically non-conductive, FM-200 works by removing heat from a fire so that combustion cannot be sustained. When it comes to being safe for use, FM-200 delivers, which is why FM-200 systems are approved by, FM and UL listed; an ideal solution where personnel safety and process continuity are paramount.

The decision to use FM-200 can be based on a number of key factors: it is the most widely used of the chemical replacements for Halon 1301 and it is an agent that has been used to successfully protect tens of thousands of high-technology facilities in 70 countries around the world.

At its design concentration, FM-200 does not sufficiently deplete the oxygen level to a point where it is unsafe for occupants to remain in the room.

FM-200 agent is stored in cylinders as a liquid, super-pressurised with nitrogen so requiring only a very small storage 'footprint'.

The discharged gas flows through a piping network into the protected area, where it is applied to suppress the fire through heat absorption.

Significantly, there is no risk of thermal shock to delicate electronic equipment and FM-200 is electrically non-conductive and non-corrosive.

Additionally, it leaves no oily residue or deposits to damage software, data files or communications equipment, meaning post-discharge clean up time and costs are minimal.

Its use as a fire suppressant is not inhibited by the Montreal Protocol. Indeed, it is a clean agent that belongs to a class of compounds that was introduced specifically to facilitate the phase-out of ozone depleting gases, such as Halon 1301.

FM-200°

Proven in thousands of successful installations worldwide

Protecting your most valuable assets

Extensively tested, FM-200 systems are proven safe for use in occupied areas. They are designed using bespoke software, which accurately calculates the amount of FM-200 required for the protected space. The target concentration of FM-200 in an identified protected volume is matched to international standards, which themselves are the result of extensive and repeated fire tests, to match design to fire protection performance.









Benefits

- Colourless, odourless, non-contaminating gaseous fire protection
- Designed to protect critical assets and processes without consequential damage
- Safe to use in occupied areas
- Tried and tested through thousands of installations around the world
- Quality and technical/service support

Applications

- Computer suites and data centres
- Offshore oil/gas exploration and production facilities
- Telecommunications centres
- Power generation
- Marine
- Museums and archives
- Data storage



Fast, effective fire protection for critical assets and processes

Full list of international approvals

Tried and trusted technology

Clean and safe solutions



Global Strength. Local Expertise.

At your service.

Offices:

Austria (Vienna)

Tel: +43 (0)1 271 0049 Fax: +43 (0)1 271 0142

Belgium (Mechelen)

Tel: +32 (0)15 285 555 Fax: +32 (0)15 206 076

Czech Republic (Liberec)

Tel: + 420 482 736 291 Fax: + 420 482 736 293

France (Paris)

Tel: +33 (0)1 48 178 727 Fax: +33 (0)1 48 178 720

Germany (Rodgau)

Tel: +49 (0)6 106 84455 Fax: +49 (0)6 106 18177 **Hungary (Budapest)**

Tel: +36 (0)1 481 1383 Fax: +36 (0)1 203 4427

Italy (Milan)

Tel: +39 (0)331 583 000 Fax: +39 (0)331 583 030

Singapore (Asia Pacific)

Tel: +65 (0)6577 4360 Fax: +65 (0)6481 8791

Spain (Madrid)

Tel: +34 (0)91 380 74 60 Fax: +34 (0)91 380 74 61

Sweden (Lammhult)

Tel: +46 (0)472 269 980 Fax: +46 (0)472 269 989 The Netherlands (Enschede)

Tel: +31 (0)53 428 4444 Fax: +31 (0)53 428 3377

Turkey (Ankara)

Tel: +90 (0)312 473 70 11 Fax: +90 (0)312 473 73 92

United Arab Emirates (Dubai)

Tel: +971 (0)4 883 8689 Fax: +971 (0)4 883 8674

United Kingdom (Manchester)

Tel: +44 (0)161 2594 000 Fax: +44 (0)161 8750 491

